

**Luminate.Doors.InColour** Care & Maintenance

Updated: Sept 2010

**Storage**

Where practical leave Luminate stored in crate that it was received in. If unpacked from crate, whenever possible store on a flat surface, if this is not possible store on the long edge leaning against a dry wall and raise from the floor on cardboard/foam or fabric. Always protect from moisture, heat and extreme climatic conditions. Store out of direct sunlight and cover.

**Cleaning**

Use warm soapy water with a cleaning cloth. Never use abrasive or solvent products to clean surfaces.

**Re-Polishing**

In most cases Ambro Luminate can be Sanded and repolished. The acrylic face is up to 2-3mm thick on average. Careful sanding will allow for the re-finishing of the product. As this process requires specific instructions please contact Ambro via our contact details found on our website [www.ambroglobal.com](http://www.ambroglobal.com).

**Minor Repairs (Scratches)**

Please note that the techniques described below are only to mask the scratches, a perfect result (eg. factory finish) can only be achieved in a factory environment

Scratches can take on two forms - those that only scratch the final coating and those that penetrate into the coloured acrylic facing.

Surface scratches - Repair by matching the colour of the finish with a permanent marker. Lightly mark the scratch with the permanent marker, removing excess with a clean rag or your finger.

Surface Penetrating Scratches – These scratches are difficult to fill, although a matching GEL Coat as used on Fibreglass could be used. If the finished coating around the scratch is visible, apply the techniques learned in the surface scratch instructions above.

**Packaging and Freight**

Doors are carefully packaged to allow for freighting to all parts of Australia and overseas. On arrival doors must be checked by the receiver and Ambro must be notified within 24hours if damage has occurred during transport.