



Ambro Luminate[®] Care & Maintenance Timber Finish



Storage

Where practical leave Luminate stored in crate that it was received in.

If unpacked from crate, whenever possible store on a flat surface, if this is not possible store on the long edge leaning against a dry wall and raise from the floor on cardboard/foam or fabric. Always protect from moisture, heat and extreme climatic conditions. Store out of direct sunlight and cover.

Installation

Follow normal door and hardware installation. Please note, as the product is pre-finished, be extra careful not to damage the product.

Any trimmed edge or machining including lock check outs should be sealed with a clear polish.

Care and cleaning

Never use abrasive or solvent products to clean surfaces; warm soapy water should suffice.

Timber Fading

This is a natural timber product therefore sunlight can fade the timber.

Re-Polishing

In most cases Ambro Luminate can be Sanded and repolished. The face of timber is up to 2-3mm thickness on average. Careful sanding will allow for the re-finishing of the product many times over its lifetime. As this process specific instructions please contact Ambro via our contact details found on our website www.ambroglobal.com.

Minor Repairs (Scratches)

Please note that the techniques described below are only to mask the scratches, a perfect result (eg. factory finish) can only be achieved in a factory environment

Scratches can take on two forms - those that only scratch the final coating and those that penetrate into the timber surface of the product itself.

Surface scratches - Repair by matching the colour of the finish with a permanent marker. Lightly mark the scratch with the permanent marker, removing excess with a clean rag or your finger. When you are satisfied with the masking of the scratch, apply AMBRO oil to the scratch, again wiping away any excess oil with a rag.

Surface Penetrating Scratches - Apply AMBRO oil to the scratch to give the timber a finished look (this should remove the raw timber look that was present after scratching). If the finished coating around the scratch is visible, apply the techniques learnt in the surface scratch instructions above..